



3 1176 00162 3637

NASA Technical Memorandum 81852

NASA-TM-81852 19800019944

POLAR SYMMETRY IN THREE-DIMENSIONAL ANALYSIS
OF LAMINATES WITH ANGLE PLIES

FOR REFERENCE
DO NOT BE TAken FROM THE ROOM

I. S. Raju and John H. Crews, Jr.

JULY 1980

JUL 16 1980



National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23665



POLAR SYMMETRY IN THREE-DIMENSIONAL ANALYSIS
OF LAMINATES WITH ANGLE PLIES

I. S. Raju
George Washington University Center
NASA Langley Research Center
Hampton, Virginia 23665

and

John H. Crews, Jr.
NASA Langley Research Center
Hampton, Virginia 23665

SCOPE

This paper discusses an improved procedure for the 3-D finite-element analysis of an angle-ply laminate with a circular hole. The procedure exploits polar symmetry and is the basis for a new finite-element computer code. For the broad class of laminates that contain angle plies, this new code requires only one-half as much computing capacity as conventional codes. Because previous 3-D analyses have been limited by computer capacity, the new code will improve the analysis of laminates with angle plies.

FINITE-ELEMENT ANALYSES

To date, only Dana and Barker [1] have presented a complete 3-D finite-element analysis of an angle-ply laminate

N80-28445 #

with a hole. They modeled one-half of the laminate thickness, exploiting midplane symmetry of their $(\pm 45^\circ)_s$ laminate. But because the 3-D stresses did not possess the usual inplane symmetry, they modeled the entire plan-view of the laminate. This approach limited their analysis to a rather coarse-grid model.

As shown in figure 1, polar symmetry can eliminate the need for complete plan-view models. The case presented in figure 1(a) is a simple $(\pm 45^\circ)_s$ laminate with a circular hole and remote, uniaxial loading. The point $A(r, \theta)$ and its polar-symmetric counterpart $A'(r, \theta+\pi)$, by inspection, have the same displacements and stresses when expressed in polar coordinates. Accordingly, the displacements for the nodes in the shaded portion of figure 1(b) can be expressed in terms of their independent, polar-symmetric counterparts. This polar symmetry reduces the required modeling to one-fourth of the laminate, the unshaded portion of figure 1(b). Polar symmetry has been used previously in plate-bending and postbuckling analyses ([2] and [3], respectively), but the current study is believed to be its first application in a 3-D stress analysis.

To verify the present use of polar symmetry, a simple case was analyzed both with and without polar symmetry

(polar symmetry required only half as many nodes). The displacements and stresses were identical, as expected.

Although the present paper deals only with the simple $(\pm 45^\circ)_s$ laminate, polar symmetry applies to the analysis of any laminate with angle plies. A finite-element computer code has been written to automatically exploit polar symmetry and is currently being used to analyze edge effects near holes. Because the new code requires only one-half as many nodes as needed previously, double the modeling refinement has been achieved for the same computing requirements.

REFERENCES

1. Jon R. Dana and Richard M. Barker, "Three-Dimensional Analysis for the Stress Distribution Near Circular Holes in Laminated Composites," VPI and SU, VPI-E-74-18, August 1974.
2. A. K. Noor and M. D. Mathers, "Finite Element Analysis of Anisotropic Plates," Int. J. Num. Methods in Eng., Vol. 11 (1977), p. 289.
3. A. K. Noor, M. D. Mathers and M. S. Anderson, "Exploiting Symmetries for Efficient Postbuckling Analysis of Composite Plates," AIAA J., Vol. 15, No. 1 (January 1977), p. 24.




Figure 1. A composite laminate and its 3-D finite-element model using polar symmetry.



1. Report No. NASA TM-81852	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle POLAR SYMMETRY IN THREE-DIMENSIONAL ANALYSIS OF LAMINATES WITH ANGLE PLIES		5. Report Date July 1980	6. Performing Organization Code
7. Author(s) I. S. Raju and John H. Crews, Jr.		8. Performing Organization Report No.	
9. Performing Organization Name and Address NASA Langley Research Center Hampton, VA 23665		10. Work Unit No. 506-53-53-01	11. Contract or Grant No.
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, DC 20546		13. Type of Report and Period Covered Technical Memorandum	14. Sponsoring Agency Code
15. Supplementary Notes			
16. Abstract This paper discusses an improved procedure for the 3-D finite-element analysis of an angle-ply laminate with a circular hole. The procedure exploits polar symmetry and is the basis for a new finite-element computer code. For the broad class of laminates that contain angle plies, this new code requires only one-half as much computing capacity as conventional codes. Because previous 3-D analyses have been limited by computer capacity, the new code will improve the analysis of laminates with angle plies.			
17. Key Words (Suggested by Author(s)) Three-dimensional stress analysis Laminates Symmetry Finite elements		18. Distribution Statement Unclassified - Unlimited Subject Category 24	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 5	22. Price* A02

* For sale by the National Technical Information Service, Springfield, Virginia 22161





